www.actsafe.ca

<u>info@actsafe.ca</u>

CATWALK SAFETY IN LIVE EVENT AND PERFORMING ARTS VENUES

November 2021

This fact sheet is intended to give information on safe work procedures when working on catwalks installed at a live event or performing arts venue.

What is a catwalk?

- An elevated platform from which many of the technical functions of a venue, such as lighting and sound, may be serviced or altered.
- Not always a solid walking surface; expanded steel, boards, and tension grids are common.
- Often located above a false or suspended ceiling.
- May have openings to access equipment or the auditorium.
- May contain lighting, audio, video, and rigging equipment.
- HVAC components may also be present.



WHAT SHOULD CATWALKS HAVE FOR SAFETY?


- ☐ Guard rails
 - ☐ Handrail located ~42" above the platform and
 - ☐ Midrail located ~21" above the platform
 - ☐ Able to withstand 125 lbs horizontally and 100 lbs downward force
- ☐ Toeboards (a.k.a. Kick Rail) to prevent objects falling to areas below
- ☐ If head bump hazards exist, they should be identified and protected where possible.
- ☐ Minimum width of 22 inches and adequate lighting (more than a penlight or 10 lumens)

- ☐ Regular inspections of catwalks (minimum of once per year) include but are not limited to:
 - ☐ Ability of the catwalk to support the weight of the work and materials
 - ☐ Anchors provided that meet the needs of your fall protection plan
 - ☐ Clear and safe access and escape routes
 - ☐ Good housekeeping (no clutter, trip hazards, or food and drink)
- ☐ Step units should all be secured from movement
- ☐ Cables should be consolidated and run overhead where possible

If you are considering adding or modifying a catwalk, please consult an engineer as catwalks are often structural members of your facility!

Handrail ~42" above platform





Toeboards (a.k.a. Kick to areas below)

Rail) to prevent objects falling

CATWALK SAFETY IN LIVE EVENT AND PERFORMING ARTS VENUES




Safe Work Practices:

- Ensure you have oriented tenants/shows/labour designees/representatives and users to the catwalk.
 - ensure they have appropriate fall protection gear and training when required.
 - include information about facility rules and possible consequences for failure to follow them.
 - all tools should be secured with a lanyard or tether to keep them from falling if dropped.
- Provide supervision at key times such as load-in, during the show, and strike.
 - maintain a list of authorized personnel who received the orientation prior to use.
 - restrict access to only those oriented and trained.
 - have trained workers shadow or supervise guest workers.
- Have a rescue plan (practiced) for workers who may be suspended after a fall.
- If guardrails must be removed for performing work:
 - assess appropriate fall protection for work with handrails removed.
 - you must be clipped in/use provided PPE.
 - ensure you replace the handrails immediately when done.










Do not use any materials or step ladders to elevate your feet off the catwalk without fall protection.

Do not sit on the catwalk with your legs over the edge.



What should I do if I have a question or think there may be a hazard?

- Report any hazards immediately to your supervisor.
- Remember you have the right to refuse unsafe work!

